

RECOMMENDED QUANTITY CHART FOR TRUCK & BUS TIRES

10 OUNCES	16 OUNCES	20 OUNCES	30 OUNCES	40 OUNCES
215 / 70R17.5	225 / 70R19.5	11R24.5	315 / 80R22.5	385 / 65R22.5
215 / 75R17.5	245 / 70R19.5	245 / 75R22.5	315 / 75R22.5	425 / 65R22.5
225 / 75R17.5	265 / 70R19.5	265 / 75R22.5		445 / 65R22.5
235 / 75R17.5	285 / 70R19.5	255 / 70R22.5		445 / 50R22.5
	305 / 70R19.5	285 / 75R24.5		445 / 65R19.5
		295 / 75R22.5		

Aluminum Wheels: Use of recommended quantity will provide adequate sealing of normal wheel porosity.



Manufactured by



www.fullerbros.com

Corporate Head Office

P.O. Box 280 | 11507 S.E. Hwy 212, Clackamas, OR 97015
Main Line +1.503.657.9366 | Toll Free +1.800.547.7785

Material safety data sheet and additional product information available on our website.



Also known as:



Maximum Tire and Rim Performance for Truck & Bus Tires





The convenient premeasured **Tire Life**® bag provides ease of use application for new and retread truck tires. **Tire Life**® is also available in bulk quantities.



www.fullerbros.com

Air Retention

- Reduces air migration through liner and bead seat area
- Reduces air loss from aluminum wheel porosity
- Reduces vent hole leaking

Retreadability

- Reduces bead brittleness
- Reduces liner oxidation
- Controls belt rust

Labor Savings

- Easier and faster dismounts
- Reduces bead chipping

Tire Life® is backed by a 100% Money Back Guarantee ensuring complete customer satisfaction