


RECOMMENDED QUANTITY CHART FOR OFF-THE-ROAD TIRES

2 GALLONS - 8 LITERS	3 GALLONS - 11 LITERS	4 GALLONS - 15 LITERS	5 GALLONS - 19 LITERS	8 GALLONS - 30 LITERS	15 GALLONS - 57 LITERS
12.00R24	18.00R25	18.00R33	24.00R35	45/65R45	37.00R57
13.00R24	21.00R25	21.00R35	33.5R35	27.00R49	42/90R57
14.00R24	20.5R25	18.00R49	29.5R35	30.00R51	
16.00R24	23.5R25	21.00R49	33.25R35	30 R 56.5	
14.00R25	26.5R25	26.5R29			20 GALLONS - 76 LITERS
16.00R25	29.5R25	29.5R29	6 GALLONS - 23 LITERS	10 GALLONS - 38 LITERS	40.00R57
15.5R25	16.9R28	33.25R29	24.00R49	33.00R51	46/90R57
17.5R25	18.4R28	23.1R26	37.5R35	36.00R51	48/95R57
14.9R24	21 L R 24	24.5R32	37.25R35	37.5R51	
16.9R24			35/65R33	50/65R51	
17.5L R 24			33.5R39		30 GALLONS - 114 LITERS
19.5L R 24			37.5R39		ALL 63"
			40.5R39		
			27 R 56.5		



QUANTITY CHART CONTINUED BELOW

Judging the correct quantity

For bias ply off the road tires add 30% more Tire Life® than recommended above. Quantities provided above are taken from an average. Each operation is different. Only you can predict your needs accurately.

How to know you have the correct amount

When the proper quantity has been applied, your tires will dismount easily, rim rust will be eliminated, and the tire inner-liner will benefit from anti-oxidant protection.

Notes

1. For best use, you should make sure your wheels/rims and tires are well cleaned prior to installing Tire Life®. Tire Life® will clean rust and corrosion from your wheels/rims through the natural washing action created by a truck in motion. Tire Life® can be installed with an applicator tank into a mounted assembly without prior cleaning, but then should be checked or changed between 30 to 90 days.
2. A good rule of thumb for judging the correct amount of Tire Life® per tire: If you dismount the tire and have 50% or more of the original install amount left in the tire then you are within good operating tolerances for the effectiveness of Tire Life®.
3. Please contact your Fuller Brothers' Representative if you have any questions or if you would like an on-site assessment and follow up recommendations.



FULLERBROS.COM

RECOMMENDED QUANTITY CHART FOR LIGHT TRUCK TIRES AND SPECIAL TRAILER TIRES PT. 1

TIRE SIZE	SECTION WIDTH (IN)	OVERALL DIAMETER (IN)	INTERNAL VOLUME (GAL)	INTERNAL VOLUME (L)	TIRE LIFE® (OZ)
LT195/75R15	7.68	26.52	5.5	20.8	5
LT205/75R15	8.07	27.11	6.2	23.4	5
LT215/75R15	8.46	27.7	6.9	26.1	5
LT225/75R15	8.86	28.29	7.7	29	10
LT235/75R15	9.25	28.88	8.5	32.1	10
LT215/85R16	8.46	30.39	7.5	28.4	10
LT225/75R16	8.86	29.29	8	30.3	10
LT235/85R16	9.25	31.73	9.2	34.9	10
LT245/75R16	9.65	30.47	9.8	36.9	10
LT255/85R16	10.04	33.07	11.2	42.4	10
LT265/75R16	10.43	31.65	11.7	44.4	10
LT285/75R16	11.22	32.83	13.9	52.7	15
LT305/70R16	12.01	32.81	15.9	60.3	15
LT315/75R16	12.4	34.6	17.7	66.8	15
LT245/70R17	9.65	30.5	9.9	37.6	10
LT245/75R17	9.65	31.47	10.2	38.5	10
LT255/80R17	10.04	33.06	11.4	43.1	10
LT265/70R17	10.43	31.61	11.9	45.1	10
LT275/70R17	10.83	32.16	13	49.2	15
LT285/70R17	11.22	32.71	14.1	53.5	15
LT285/75R17	11.22	33.83	14.5	54.7	15
LT295/70R17	11.61	33.26	15.3	58	15
LT315/70R17	12.4	34.36	17.9	67.6	20
LT265/65R18	10.43	31.56	12.1	45.9	10
LT275/65R18	10.83	32.07	13.2	50	15



FULLERBROS.COM

RECOMMENDED QUANTITY CHART FOR LIGHT TRUCK TIRES AND SPECIAL TRAILER TIRES PT. 2

TIRE SIZE	SECTION WIDTH (IN)	OVERALL DIAMETER (IN)	INTERNAL VOLUME (GAL)	INTERNAL VOLUME (L)	TIRE LIFE® (OZ)
LT275/70R18	10.83	33.16	13.5	51.1	15
LT285/65R18	11.22	32.59	14.3	54.3	15
LT295/70R18	11.61	34.26	15.9	60.2	20
LT325/65R18	12.8	34.63	19.4	73.6	20
LT265/60R20	10.43	32.52	12.8	48.5	10
LT275/55R20	10.83	31.91	13.6	51.5	15
LT275/65R20	10.83	34.07	14.2	53.9	15
LT285/55R20	11.22	32.34	14.8	55.9	15
LT295/60R20	11.61	33.94	16.3	61.8	15
LT305/55R20	12.01	33.21	17.2	65.1	20
LT325/60R20	12.8	35.35	20.4	77.1	20
ST145/80R12	5.71	21.13	2.4	9.2	5
ST175/80R13	6.89	24.02	4	15	5
ST185/80R13	7.28	24.65	4.5	17.1	5
ST205/75R14	8.07	26.11	5.9	22.3	5
ST215/75R14	8.46	26.7	6.6	24.9	10
ST205/75R15	8.07	27.11	6.2	23.4	5
ST225/75R15	8.86	28.29	7.7	29	10
ST235/75R15	9.25	28.88	8.5	32.1	10
ST225/70R15	8.86	27.4	7.5	28.4	10
ST235/80R16	9.25	30.8	9	34.2	10
ST235/85R16	9.25	31.73	9.2	34.9	10
ST215/75R17.5	8.46	30.2	7.7	29.1	10
ST235/75R17.5	9.25	31.38	9.4	35.6	10
ST245/75R17.5	9.65	31.97	10.4	39.2	10