



Farm / Ag





Advantages/Value

- Stops rim rust
Makes tire change out and clean up safer and quicker
Reduces wear and tear on tools, equipment, and service technicians
- Coats and protects tire's inner liner
Reduces air migration through liner and bead seat area
- Leak detector
Quickly identify problem areas
- Keeps tires running cooler when roading equipment
- Environmentally safe
Non-toxic / Non-hazardous

See Next Page for Farm /Ag Quantity Chart

Tire Life® Quantities Explained

Fuller Brothers' quantity charts were developed and have been changed over the last 50 years to reflect our "BEST ESTIMATE" for tires in hundreds of applications in places all over the world. For this reason our chart is only a guide. Our expert dealers in the field know the requirements at each individual site and understand their respective operation in its entirety.

Notes and Guidelines

- After Tire Life® is installed and the tire has reached the end of its usable life there should be at least 50% of the product left in the tire's air chamber. Example: 10 gallons installed when new, there should be 5 gallons (approximately) when the tire reaches the end of its life cycle.
- Time in use - some tires remain on machines an extremely long time, this should also be considered.
- In some cases Tire Life® should be added during the tire's life cycle.
- Bias tires may require up to a 30% increase in quantity (rule above is still applicable).
- Previous rust build-up could require increased quantity.
- If requested, on-site assessments are always available.

Safety data sheet and additional product information available on our website.



RECOMMENDED QUANTITY CHART FOR FARM /AG TIRES

Tire Size	Tire Life® Gallons	Tire Size	Tire Life® Gallons	Tire Size	Tire Life® Gallons
11.2-28	2	23.1-30	5	385/85R34MPT	3
11.2-29	2	23.1-34	5	420/70R24	2
11.2-30	2	24.5-32	6	420/70R28	2
11.2-31	2	240/70R16	0.5	420/80R46	3
11.2-32	2	250/80R16	0.5	420/85R28	3
11.2-33	3	250/80R18	0.5	420/90R30	3
11.2-34	2	250/95R34	2	480/70R28	3
11.2-35	2	250/95R50	2	480/70R30	3
11.2-36	2	260/70R16	0.5	480/70R34	3
11.2-37	2	260/80R20	0.5	480/80R38	4
11.2-38	3	28L-26	5	480/80R42	4
11.2-39	3	290/90R38	2	480/80R46	4
14.9-46	3	290/95R34	5	480/80R50	4
15.5-38	3	30.5L-32	7	480/85R34	4
16.9-24	3	320/70R24	2	VA500/95D32	5
16.9-26	3	320/75R24	2	520/85R38	5
16.9-28	3	320/80R42	2	520/85R42	5
16.9-30	3	320/85R34	2	520/85R46	5
16.9-34	3	320/85R38	2	540/65R30	3
16.9-38	3	320/90R42	2	580/70R38	5
17.5L-24	2	320/90R46	2	600/65R28	4
18.4-26	3	320/90R50	2	620/70R42	6
18.4-28	3	320/90R54	2	620/70R46	6
18.4-30	3	340/80R18	2	620/75R32	4
18.4-34	4	340/85R46	3	650/65R42	5
18.4-38	4	35.5L-32	8	650/75R32	5
18.4-42	4	380/70R20	2	650/75R34	6
18.4-46	4	380/70R24	2	650/85R38	7
19.5L-24	3	380/70R28	2	710/70R38	6
20.8-34	4	380/80R38	2	710/70R42	7
20.8-38	5	380/85R28	2	750/65R26	5
20.8-42	5	380/85R30	2	800/65R32	6
20.8-46	5	380/85R34	2	800/70R38	8
21L-24	3	380/90R46	3	900/50R42	7
21L-28	4	380/90R50	3	900/60R32	8
23.1-26	4	380/90R54	3	900/65R32	8

Corporate Head Office