



Rail & Port Container Handlers



Features – Rail & Port Container Handlers



- Stops rim rust
Makes change out and clean up safer and quicker
Reduces wear and tear on tools, equipment, and service technicians
- Coats and protects tire's inner liner
Reduces air migration through liner and bead seat area
- Leak Detector
Quickly identify problem areas
- Keeps tires running cooler
- 100% environmentally safe
Non-toxic / Non-hazardous

Size	Gallons	Gallons High Heat Application
16.00R25	2	3
29.5R25	3	5
29.5R29	4	5
33.25R29	4	5
18.00R25	3	5
18.00R33	4	6
24.00R35	5	7
27.00R49	8	12
33.00R51	10	15
36.00R51	10	15
40.00R57	20	30

How to know you are right

When the proper quantity has been applied, your tires will dismount easily, rim rust will be eliminated, and the tire inner-liner will benefit from anti-oxidant protection.

Notes:

1. For best use, you should make sure your wheels/rims and tires are well cleaned prior to installing Tire Life®. Tire Life® will clean rust and corrosion from your wheels/rims through the natural washing action created by a truck in motion. Tire Life® can be installed with an applicator tank into a mounted assembly without prior cleaning, but then should be checked or changed between 30 to 90 days.
2. A good rule of thumb for judging the correct amount of Tire Life® per tire: If you dismount the tire and have 50% or more of the original install amount left in the tire then you are within good operating tolerances for the effectiveness of Tire Life®.
3. Please contact your Fuller Brothers' Representative if you have any questions or if you would like an on-site assessment with follow up recommendations.

FULLER BROTHERS, INC.
www.fullerbros.com

Corporate Head Office

P.O. Box 280 | 11507 S.E. Hwy 212, Clackamas, OR 97015
 Main Line +1.503.657.9366 | Toll Free +1.800.547.7785

